

USAlert WatchDog™ LT

USAlert's continuation of
advanced paging products and
service excellence™

The **WatchDog LT** is the newest member of our family of loud and rugged voice pagers. A more simplified version of the original WatchDog, the LT is a more compact, lightweight option with 1 or 2 channels.

With a 4 position switch, the LT offers very simple to use, preprogrammed user function switches.

Choice of tone alert, vibrate alert, or simultaneous tone and vibrate. On/Off Duty capability. Up to four minutes of stored voice.

The Watchdog LT has an IP66 Rating. Total protection against dust and powerful water jets from any direction.



A man's best friend is his dog
a fireman's best friend is his **WatchDog™ LT**

Assembled in the United States of America

OSI International, LLC.
164 West Royal Palm Road
Boca Raton, FL 33432
561. 394. 9508
www.osiinternational.com

Synthesized and Up to 2 Channel

WATCHDOG™ LT

Features:

- Two Tone Decoding Format
- 15 Addresses Per Channel
- Optional 1 or 2 Channel
- Tone Alert, Vibrate Alert or Tone-Vibe alert
- On / Off Volume Control
- Quick Monitor Control
- Audio Lock On
- Multi Function Scan
 - Channel Scan
 - Selective Call Scan
 - Priority Scan
- Low Battery Alert
- Wideband and Narrowband Models
- 4 Minutes Voice Memory
- Forward Message Playback Select
- Reverse Message Playback Select
- Delete Message
- Delete all Messages
- 3 Bar Graphic Battery Level Indication
- AAA Rechargeable Batteries included
- Compatible w/ Alkaline Batteries as well

Band	VHF	UHF
Frequency Range MHz	138 - 174	406 - 512
Frequency Stability	+/- 0.0010%	+/- 0.0005%
Channel Spacing	12.5 KHz / 25 KHz	12.5 KHz / 25 KHz
Sensitivity / Alerting	2.0 uV/m	3.5 uV/m
Sensitivity / 12dB SINAD	4uV/m	10uV/m
Adjacent Channel Selectivity	65dB	65dB
Spurious & Image Rejection	>55dB	>55dB
Audio Output Linear	> 750 mw	> 750 mw
Alert	102 dB SPL @ 12"	102 dB SPL @ 12"
Voice	98dB SPL @ 12"	98dB SPL @ 12"
Audio Distortion	< 2%	< 2%
Battery Life NiMH	5 days	5 days
Battery Life Alkaline	7 days	7 days
Dimensions	3.9" X 2.25" X 1.0"	3.9" X 2.25" X 1.0"
Weight	175g	175g