

TPL Birdy Slim Alphanumeric Pager Specification Sheet



SPECIFICATION	VHF	UHF
Pager Type	Alphanumeric	Alphanumeric
Code Format	Pocsag	Pocsag
Baud Rate	512 / 1200 / 2400	512 / 1200 / 2400
Frequency Range	136 - 174 MHz	426 - 474 MHz
Alerting Sensitivity	512 ≤ 2 u/Vm	512 ≤ 2 u/Vm
	1200 ≤ 2.5 u/Vm	1200 ≤ 2.5 u/Vm
	2400 ≤ 3 u/Vm	2400 ≤ 3 u/Vm
Selectivity (Wide Band)	65 dB	65 dB
Intermodulation Rejection	65 dB	65 dB
Frequency Stability	≤ ± 8 ppm	≤ ± 8 ppm
Channel Spacing	12.5 / 20 / 25 KHz	
Receiver Type	Synthesized	
Programmable Addresses	128	
LCD Display	8 Lines, 16 Chars/Line, Multi-color Backlight, Modifiable Zoom	
Alert Tone SPL	86 dB @ 30 cm (12")	
Operating Temperature	-10 C to 60 C	
Storage Temperature	-10 C to 70 C	
Battery Type	Rechargeable 3.7 VDC / 800 mA Li-Ion	
Weight	90 grams (3.2 oz)	
Dimensions	97.4 X 54.7 X 16.7 mm (3.8 X 2.2 X 0.7 inch)	