



NUMERIC MESSAGING  
ONE WAY PAGER  
NP-88

# Great Things Come From Small Packages



## Unication Numeric Pager

The NP-88 offers accessibility to stay on top of your busy lifestyle. Perfect for basic wireless communication and user-friendly operation. You can set the pager to generate an audible or a vibration alert no matter under noisy or quiet environments when you are expecting an important page. The NP-88 is compact, lightweight, inexpensive, and the best choice when you need reliable paging with broad coverage.

## NUMERIC PAGER

### Model Type

NP-88 Numeric Pager FLEX

Synthesized



## FEATURE LIST:

### DISPLAY:

- \* Backlight  
In low-light conditions, the backlight makes the screen easy to read.
- \* Standby Screen  
The standby screen displays the time of day/date or no display.
- \* Time of Day and Day/Month  
The time of day and the date display whether the pager is on or off.

### INDICATORS/ ALERT:

- \* Low Battery Indicator  
When battery power reaches low levels, low cell is displayed, prompting you to change the battery. All pager alerts change to two seconds in length.
- \* Automatic Alert Reset  
The pager alerts automatically stop, even if no buttons are pressed.
- \* Personal Alarm  
This alarm can be set to alert you. The alarm works even when the pager is off.
- \* Reminder Alert  
The pager chirps or vibrates every two minutes until you read all unread messages.
- \* User Selectable Audible Alerts  
A selection of five alert tones give you a choice of message alerts heard when you are paged in the audible alert mode D.

### MESSAGING:

- \* Duplicate Messages  
If the same message is received more than once, duplicate sign is displayed at the beginning of the latest message. This message contains the latest timestamp and prevents a repeated message from taking an extra memory slot.
- \* Message Erase  
Messages can be erased all at once or selectively at your choice to free space in memory.
- \* Memory Retention  
All messages remain in memory, even when the pager is off and while the battery is being replaced.
- \* Memory Capacity  
The NP88 FLEX pager can store up to sixteen 20-character messages, for a total of 320 characters.
- \* Message Protect  
You can protect up to eight messages stored in the pager memory.
- \* Overflow  
Overflow is displayed when more unread messages are received than the available message memory can hold. After you read all of your unread messages, the standby screen is displayed.
- \* Timestamp  
The time and the date of a message received are displayed on the screen after each message.

For more information, please contact

For more information, please contact

**OSI International, LLC**  
1809 S. Powerline Rd., Suite 101  
Deerfield Beach, FL 33442  
Sales: (866) 394-9508  
Fax: (561) 394-9354  
Web: [www.osiinternational.com](http://www.osiinternational.com)  
Email: [info@osiinternational.net](mailto:info@osiinternational.net)

## NP-88

### Product Specifications

Band splits	VHF	900 MHz
Frequency Range	137~143MHz 143~153MHz 153~163MHz 163~174MHz	929-932 MHz
Baud Rate (bps)	1600, 3200, 6400	
Code Format	FLEX	
Paging Sensitivity (uVm) Best Position Maximum	Baud 1600 : $\leq 8$ uVm Baud 3200: $\leq 11$ uVm Baud 6400: $\leq 13.5$ uVm	
Selectivity	$\geq 55$ dB	$\geq 40$ dB
Spurious & Image Rejection	$\geq 40$ dB	$\geq 40$ dB
Frequency Stability	$\leq \pm 15$ ppm	$\leq \pm 3.5$ ppm
Channel Spacing	25 kHz	
Receiver Type	Synthesized	
Address Capability	2 FLEX address	
Frequency Deviation	$\pm 4.8$ kHz	
Alert Tone	$\geq 78$ dB @ 12 in (2700 Hz Standard Alert)	
Operating Temperature	5 ° to 40 ° C	
Storage Temperature	-40 ° to +85 ° C	
Power Supply	One 1.5V, AAA Alkaline Battery	
Battery Life ( Estimated battery life is based on full battery capacity and 2 pages/day)	Auto Baud Detect Collapse = 4 90days	
Low Battery Alert level	1.2Volts	
Weight with Battery	60g	
Dimensions	63.65 x45.0 x17.5mm (2.50 x1.77 x0.69 in)	



**Corporate Headquarters:**  
Unication Co., Ltd.,  
5F., No. 6, Wu-Kung 5Rd., Hsinchuang City,  
Taipei, Taiwan. R.O.C.  
Phone: + 886 2 2299 9678  
Fax: +886 2 2299 7998  
Email: [salesenquiry@uni.com.tw](mailto:salesenquiry@uni.com.tw)

**Dallas Sales Office:**  
Unication USA Inc.  
1901 E. Lamar Blvd.,  
Arlington, TX 76006, U.S.A.  
Phone: 817-303-9320  
Fax: 817-886-3424  
Email: [sales@uniamericas.com](mailto:sales@uniamericas.com)



[www.uni.com.tw](http://www.uni.com.tw)