



NUMERIC MESSAGING
ONE WAY PAGER
NP-88

Great Things Come From Small Packages



Unication Numeric Pager

The NP-88 offers accessibility to stay on top of your busy lifestyle. Perfect for basic wireless communication and user-friendly operation. You can set the pager to generate an audible or a vibration alert no matter under noisy or quiet environments when you are expecting an important page. The NP-88 is compact, lightweight, inexpensive, and the best choice when you need reliable paging with broad coverage.

NUMERIC PAGER

Model Type

NP-88 Numeric Pager POCSAG

Synthesized



FEATURE LIST:

DISPLAY:

- * Backlight
In low-light conditions, the backlight makes the screen easy to read.
- * Standby Screen
The standby screen displays the time of day/date or no display.
- * Time of Day and Day/Month
The time of day and the date display whether the pager is on or off.

INDICATORS/ ALERT:

- * Low Battery Indicator
When battery power reaches low levels, low cell is displayed, prompting you to change the battery. All pager alerts change to two seconds in length.
- * Automatic Alert Reset
The pager alerts automatically stop, even if no buttons are pressed.
- * Personal Alarm
This alarm can be set to alert you. The alarm works even when the pager is off.
- * Reminder Alert
The pager chirps or vibrates every two minutes until you read all unread messages.
- * User Selectable Audible Alerts
A selection of five alert tones give you a choice of message alerts heard when you are paged in the audible alert mode D.

MESSAGING:

- * Duplicate Messages
If the same message is received more than once, duplicate sign is displayed at the beginning of the latest message. This message contains the latest timestamp and prevents a repeated message from taking an extra memory slot.
- * Message Erase
Messages can be erased all at once or selectively at your choice to free space in memory.
- * Memory Retention
All messages remain in memory, even when the pager is off and while the battery is being replaced.
- * Memory Capacity
The NP88 POCSAG pager can store up to sixteen 20-character messages, for a total of 320 characters.
- * Message Protect
You can protect up to eight messages stored in the pager memory.
- * Overflow
Overflow is displayed when more unread messages are received than the available message memory can hold. After you read all of your unread messages, the standby screen is displayed.
- * Timestamp
The time and the date of a message received are displayed on the screen after each message.

For more information, please contact

For more information, please contact

OSI International, LLC
1809 S. Powerline Rd., Suite 101
Deerfield Beach, FL 33442
Sales: (866) 394-9508
Fax: (561) 394-9354
Web: www.osiinternational.com
Email: info@osiinternational.net

NP-88

Product Specifications

Band splits	VHF	UHF	900 MHz
Frequency Range	137 – 143MHz 143 – 153MHz 153 – 163MHz 163 – 174MHz	450 – 460MHz 460 – 470MHz	929 – 932MHz
Baud Rate (bps)	512, 1200, 2400 bps		
Code Format	POCSAG CCIR No. 1		
Paging Sensitivity (µV/m) (typical/maximum µV per meter unless otherwise noted):	512.bps: ≤ 5 uV/m 1200.bps: ≤ 7 uV/m 2400.bps: ≤ 10 uV/m	512.bps: ≤ 6 uV/m 1200.bps: ≤ 8 uV/m 2400.bps: ≤ 10 uV/m	512.bps: ≤ 6 uV/m 1200.bps: ≤ 8 uV/m 2400.bps: ≤ 10 uV/m
Selectivity	≥ 60 dB	≥ 55 dB	≥ 50 dB
Frequency Stability	+/- 15 ppm	+/- 5 ppm	+/- 3.5 ppm
Spurious Rejection	≥ 50 dB		40 dB below carrier
Alert Tone	78 dB @ 12 inches (2730 Hz Standard Alert)		
Operating Temperature	5 °C to 40 °C (40 °F to 105 °F)		
Channel Spacing	25 kHz		
Frequency Deviation	+/- 4.5 kHz		
Power Supply	One 1.5V, AAA-size Alkaline Battery		
Battery Life (Based on 2 pages/day; 24 hour ON; full-capacity alkaline battery)	512 Baud: ≈ 25 days 1200 Baud: ≈ 23 days 2400 Baud: ≈ 20 days		
Weight with Battery	60g		
Dimensions	63.65 x45.0 x17.5mm(2.50 x1.77 x0.69in)		



Corporate Headquarters:
Unication Co., Ltd.,
5F., No. 6, Wu-Kung 5Rd., Hsinchuang City,
Taipei, Taiwan. R.O.C.
Phone: + 886 2 2299 9678
Fax: +886 2 2299 7998
Email: salesenquiry@uni.com.tw

Dallas Sales Office:
Unication USA Inc.
1901 E. Lamar Blvd.,
Arlington, TX 76006, U.S.A.
Phone: 817-303-9320
Fax: 817-886-3424
Email: sales@uniamericas.com

www.uni.com.tw

