

TPL Birdy 3G Alphanumeric Pager Specification Sheet



SPECIFICATION	VHF	UHF
Pager Type	Alphanumeric	Alphanumeric
Code Format	Pocsag / Flex	Pocsag / Flex
Baud Rate	Pocsag 512 / 1200 / 2400 Flex 1600 3200 6400	Pocsag 512 / 1200 / 2400 Flex 1600 3200 6400
Frequency Range	All VHF Frequencies	UHF Frequencies upon request
Alerting Sensitivity Pocsag	1200 \leq 3 u/Vm	1200 \leq 3 u/Vm
Alerting Sensitivity Flex	1600 \leq 3 u/Vm	1600 \leq 3 u/Vm
Selectivity (Wide Band)	65 dB	65 dB
Intermodulation Rejection	65 dB	65 dB
Frequency Stability	$\leq \pm 10$ ppm	$\leq \pm 10$ ppm
Channel Spacing	12.5 / 20 / 25 KHz	
Receiver Type	Synthesized	
Programmable Addresses	128	
LCD Display	4 Lines, 20 Chars/Line, Modifiable Zoom	
Alert Tone SPL	86 dB @ 30 cm (12")	
Operating Temperature	-20 C to 60 C	
Storage Temperature	-20 C to 70 C	
Battery Type	Rechargeable 3.7 VDC / 1300 mA Li-Ion	
Weight	120 grams (4.2 oz)	
Dimensions	94 X 59.5 X 21.5 mm (3.7 X 2.3 X 0.8 inch)	